



# Safety Data Sheet

## I. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** PRIME GRD 85W140 GL5 55GL  
**Product Code:** PF051455 PG85W14055  
**Emergency Phone:** CHEMTREC: +1 (800) 424-9300  
International: +01 (703) 527-3887  
**Poison Control Center:** (800) 222-1222  
**Company:** Prime Guard  
8295 Tournament Dr. Ste 150  
Memphis, TN 38125  
**Information Phone:** (662) 874-1283  
**E-mail:** sds@wd-wpp.com

## II. HAZARDS IDENTIFICATION

**Routes of Entry:** Skin contact  
**Target Organs:** Skin  
**Chemical Interactions:** No chemical interaction known to affect toxicity.  
**Conditions Aggravated by Exposure:** Personnel with pre-existing skin disorders should avoid contact with this product.

### Acute Health Effects:

**Inhalation Irritation:** Breathing oil mist in concentrations that exceed the TLV and PEL may result in respiratory discomfort and irritation.  
**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis. May cause skin irritation.  
**Skin Absorption:** Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.  
**Eye Contact:** Lubricating oils are generally considered no more than minimally irritating to the eyes.  
**Ingestion Irritation:** No hazard in normal industrial use. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

### Chronic Health Effects:

**Carcinogenicity:** Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.  
**Reproductive Toxicity:** No data available to indicate product or any components present at greater than 0.1% may cause birth defects.  
**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

#### HMIS Ratings:

Health: 1  
Fire: 1  
Reactivity: 0  
PPE: B

#### NFPA Ratings:

Health: 1  
Fire: 1  
Reactivity: 0

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

## III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #	OSHA Exposure Limits
Residual oils, petroleum, solvent-refined	90 - 99	64742-01-4	
Petroleum distillates, hydrotreated heavy paraffinic	5 - 10	64742-54-7	5 mg/m3

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

# Safety Data Sheet

## IV. FIRST-AID MEASURES

---

<b>Inhalation:</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen and get medical attention immediately.
<b>Eyes:</b>	Flush with water. If irritation occurs, get medical attention. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling occurs, transport to nearest medical facility for additional treatment.
<b>Skin Contact:</b>	Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If redness, swelling, pain, and/or blisters occur, transport to the nearest medical facility for additional treatment. Seek medical advice if symptoms persist.
<b>Ingestion:</b>	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
<b>Notes to Doctor:</b>	Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

## V. FIRE FIGHTING MEASURES

---

<b>Flammability</b>	Combustible at elevated temperatures
<b>Summary:</b>	
<b>Extinguishing Media:</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
<b>Fire and/or Explosion Hazards:</b>	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
<b>Fire Fighting Methods and Protection:</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.
<b>Hazardous Combustion Products:</b>	Carbon monoxide, Smoke

## VI. ACCIDENTAL RELEASE MEASURES

---

<b>Personal Precautions and Equipment:</b>	No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS.
<b>Methods for Clean-up:</b>	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Remove from water surface by skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm sewers and ditches that lead to waterways. Do not flush to sewer.

## VII. HANDLING AND STORAGE

---

<b>Handling Precautions:</b>	Mildly irritating material. Avoid unnecessary exposure.
<b>Storage Conditions:</b>	Store in a cool dry place. Isolate from incompatible materials.

## VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

<b>Engineering Controls:</b>	No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.
<b>Respiratory Protection:</b>	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate

# Safety Data Sheet

symptoms.

**Respirator Type(s):** None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

**Eye Protection:** Wear safety glasses when handling this product if there is a likelihood of contact with eyes.

**Skin Protection:** Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

**Gloves:** Neoprene, Nitrile

## Control Parameters:

Chemical Name	ACGIH TLV -TWA	ACGIH STEL	IDLH	NIOSH STEL
Residual oils, petroleum, solvent-refined Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3	10 mg/m3		

## X. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid

**Color:** Brown

**Odor:** Mild

**pH:** Not determined

**Viscosity (cSt at 40°C):** 347.7

**Solubility in Water:** Negligible; 0-1%

**Octanol/Water** Not determined

**Partition Coefficient:**

**Evaporation Rate:** Not determined

**Vapor Density:** Not determined

**Vapor Pressure:** <0.20

**Boiling Point (°C):** Not determined

**Freezing Point (°C):** Not determined

**Specific Gravity:** 0.9

**Density:** 7.49

**Flash Point (°C):** 218

**Flash Point Method:** COC

**Upper Flammability Limit, % in air:** Not established

**Lower Flammability Limit, % in air:** Not established

## X. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions. Hazardous polymerization will not occur

**Conditions to Avoid:** Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).

**Materials to Avoid:** Strong oxidizing agents

**Hazardous Decomp. Products:** Carbon monoxide, Smoke

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## XI. TOXICOLOGICAL INFORMATION

### Acute Toxicity:

**Ingestion:** Although this product has a low order of acute oral toxicity, aspiration of minute

# Safety Data Sheet

amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

**Inhalation:** Harmful! Can cause systemic damage (see "Target Organs").  
**Absorption:** Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.  
**Eyes:** The material is likely to be moderately irritating to eyes based on animal data.  
**Skin:** This material is likely to be moderately irritating to skin based on animal data.  
**Sensitization:** No data available to indicate product or components may be a skin sensitizer.

## Component Toxicology Data:

<b>Chemical Name</b>	<b>CAS #</b>	<b>LD<sub>50</sub>/LC<sub>50</sub></b>
Residual oils (petroleum), solvent-refined	64742-01-4	Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Polysulfides, di-tert-butyl	68937-96-2	Oral LD50 Rat 6500 mg/kg (Source: IUCLID)

## XII. ECOLOGICAL INFORMATION

**Overview:** Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.  
**Mobility:** This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.  
**Persistence:** Biodegradation, adsorption to sediment, and bioconcentration to aquatic organisms should not be significant.  
**Bioconcentration:** Bioconcentration may occur.  
**Degradability:** Biodegrades slowly.

<b>Toxicity to Aquatic Invertebrates:</b>	<b>CAS #</b>	<b>Results</b>
Residual oils (petroleum), solvent-refined	64742-01-4	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	48 Hr EC50 Daphnia magna: >1000 mg/L
<b>Toxicity to Fish:</b>	<b>CAS #</b>	<b>Results</b>
Residual oils (petroleum), solvent-refined	64742-01-4	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Polysulfides, di-tert-butyl	68937-96-2	96 Hr LC50 Pimephales promelas: 250 - 500 mg/L [static]; 96 Hr LC50 Pimephales promelas: >1000 mg/L [semi-static]

## XIII. DISPOSAL CONSIDERATIONS

**Disposal of Packaging:** Recycle containers whenever possible.  
**Disposal Methods:** Dispose of by incineration following Federal, State, Local, or Provincial regulations.

## XIV. TRANSPORTATION INFORMATION

**D.O.T.** Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

# Safety Data Sheet

## XV. REGULATORY INFORMATION

---

**TSCA Status:** All components of this material are on the US TSCA Inventory or are exempt.  
**State Restrictions:** Not applicable  
**WHMIS:** Uncontrolled product according to WHMIS classification criteria.

Chemical Name	Regulation	CAS #	% Range
None.	CERCLA RQ		
Vinyl acetate	SARA 313	108-05-4	0.001- 0.01
Cumene	SARA 313	98-82-8	0.001- 0.01
ethylbenzene	SARA 313	100-41-4	0.001- 0.01
Naphthalene	SARA 313	91-20-3	<10ppm
Methyl isobutyl ketone	SARA 313	108-10-1	<10ppm
Ethyl acrylate	SARA 313	140-88-5	<10ppm
None.	SARA 302-EHS		
None.	TSCA 12b export notification		
Cumene	CA Prop 65 – Cancer	98-82-8	0.001- 0.01
ethylbenzene	CA Prop 65 – Cancer	100-41-4	0.001- 0.01
Naphthalene	CA Prop 65 – Cancer	91-20-3	<10ppm
ISOBUTYL METHYL KETONE	CA Prop 65 – Cancer	108-10-1	<10ppm
Ethyl acrylate	CA Prop 65 – Cancer	140-88-5	<10ppm
None.	CA Prop 65 - Dev. Toxicity		
None.	CA Prop 65 - Reprod –fem		
None.	CA Prop 65 - Reprod –male		
None.	Canadian WHMIS List		
None.	Massachusetts RTK List		
None.	New Jersey RTK List		
None.	Pennsylvania RTK List		
None.	Minnesota Hazardous Substance List		

### Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

## XVI. ADDITIONAL INFORMATION

---

**Supersedes:** 8/27/2014 5:04:08 PM

**Revision Date:** 9/4/2014 12:58:43 PM

**Disclaimer:** This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.