



Safety Data Sheet

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PRIME 10W30 FS 6/1QT
Product Code: PF13FHP6 PGSYN1030
Emergency Phone: CHEMTREC: +1 (800) 424-9300
International: +01 (703) 527-3887
Poison Control Center: (800) 222-1222
Company: Prime Guard
8295 Tournament Dr. Ste 150
Memphis, TN 38125
Information Phone: (662) 874-1283
E-mail: sds@wd-wpp.com

II. HAZARDS IDENTIFICATION

Routes of Entry: Skin contact
Target Organs: Skin, Eyes, Respiratory Tract, Lungs
Chemical Interactions: No chemical interaction known to affect toxicity.
Conditions Aggravated by Exposure: Personnel with pre-existing skin disorders should avoid contact with this product., Lung disease, Skin disease including eczema and sensitization, Respiratory disease including asthma and bronchitis, Eye disease

Acute Health Effects:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. May cause skin irritation.
Skin Absorption: No absorption hazard in normal industrial use.
Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Chronic Health Effects:

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

HMIS Ratings:

Health: 2
Fire: 1
Reactivity: 0
PPE: B

NFPA Ratings:

Health: 2
Fire: 1
Reactivity: 0

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

Safety Data Sheet

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #	OSHA Exposure Limits
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	90 - 99	72623-87-1	5 mg/m ³
Petroleum distillates, solvent dewaxed heavy paraffinic	1 - 5	64742-65-0	5 mg/m ³
Petroleum distillates, hydrotreated heavy paraffinic	1 - 5	64742-54-7	5 mg/m ³
Mineral oil	0.1 - 1	8012-95-1	5 mg/m ³ TWA

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

IV. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
Eyes:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Seek medical advice if symptoms persist.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal. Contains a harmful substance. Seek medical help immediately and contact a poison information service. Drink two glasses of water or milk to dilute.
Notes to Doctor:	Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

V. FIRE FIGHTING MEASURES

Flammability	Combustible at elevated temperatures
Summary:	
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Fire and/or Explosion Hazards:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Fire Fighting Methods and Protection:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.
Hazardous Combustion Products:	Carbon dioxide, Carbon monoxide

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Remove from water surface by skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm sewers and ditches that lead to waterways. Do not flush to sewer.

Safety Data Sheet

VII. HANDLING AND STORAGE

Handling Precautions: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer.

Storage Conditions: Store in a cool dry place. Isolate from incompatible materials.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or using this material should be equipped with an eyewash and safety shower.

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Wear a NIOSH approved respirator if any exposure is possible.

Respirator Type(s): None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Wear goggles and a Face shield.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

Gloves: Nitrile

Control Parameters:

Chemical Name	ACGIH TLV -TWA	ACGIH STEL	IDLH	NIOSH STEL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	5 mg/m3	10 mg/m3		
Petroleum distillates, solvent dewaxed heavy paraffinic	5 mg/m3	10 mg/m3		
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3	10 mg/m3		
Mineral oil	5 mg/m3 TWA (excluding metal working fluids, highly & severely refined, inhalable fraction)		2500 mg/m3 IDLH	10 mg/m3 STEL

X. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Color: Amber
Odor: Mild
pH: Not determined
Viscosity (cSt at 61.47

Safety Data Sheet

40°C):

Solubility in Water:	Negligible; 0-1%
Octanol/Water Partition Coefficient:	Not determined
Evaporation Rate:	Not determined
Vapor Density:	Not determined
Vapor Pressure:	Not determined
Boiling Point (°C):	Not determined
Freezing Point (°C):	Not determined
Specific Gravity:	0.86
Density:	7.14
Flash Point (°C):	220
Flash Point Method:	COC
Upper Flammability Limit, % in air:	Not established
Lower Flammability Limit, % in air:	Not established

X. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions. Hazardous polymerization will not occur
Conditions to Avoid:	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Materials to Avoid:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon monoxide, sulfur oxides, aldehydes, and other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present.
Hazardous Polymerization:	Hazardous polymerization will not occur.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Ingestion:	Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.
Inhalation:	Harmful! Can cause systemic damage (see "Target Organs").
Absorption:	No absorption hazard in normal industrial use.
Eyes:	This material is estimated to be non-irritating eyes (Draize score <15 [rabbits]).
Skin:	This material is likely to be slightly irritating to skin based on animal data.
Sensitization:	No data available to indicate product or components may be a skin sensitizer.

Component Toxicology Data:

Chemical Name	CAS #	LD₅₀/LC₅₀
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Mineral oil	8012-95-1	Inhalation LC50 Rat 2062 ppm 4 h (Source: NLM_CIP)

Safety Data Sheet

XII. ECOLOGICAL INFORMATION

Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
Mobility:	This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
Persistence:	Biodegradation, adsorption to sediment, and bioconcentration to aquatic organisms should not be significant.
Bioconcentration:	Bioconcentration may occur.
Degradability:	Biodegrades slowly.

Toxicity to Aquatic Invertebrates:	CAS #	Results
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	48 Hr EC50 Daphnia magna: >1000 mg/L

Toxicity to Fish:	CAS #	Results
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L

XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging:	Recycle containers whenever possible.
Disposal Methods:	Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil.

XIV. TRANSPORTATION INFORMATION

D.O.T.	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).
---------------	--

XV. REGULATORY INFORMATION

TSCA Status:	All components of this material are on the US TSCA Inventory or are exempt.
State Restrictions:	Not applicable
WHMIS:	Uncontrolled product according to WHMIS classification criteria

Chemical Name	Regulation	CAS #	% Range
None.	CERCLA RQ		
None.	SARA 313		
None.	SARA 302-EHS		
None.	TSCA 12b export notification		
None.	CA Prop 65 – Cancer		
None.	CA Prop 65 - Dev. Toxicity		
None.	CA Prop 65 - Reprod –fem		
None.	CA Prop 65 - Reprod –male		
Mineral oil	Canadian WHMIS List	8012-95-1	0.1 - 1
Oil, mineral	Massachusetts RTK List	8012-95-1	0.1 - 1
Mineral oils, highly-refined	New Jersey RTK List	8012-95-1	0.1 - 1
Mineral oil	Pennsylvania RTK List	8012-95-1	0.1 - 1

Safety Data Sheet

Chemical Name	Regulation	CAS #	% Range
Oil mist, mineral	Minnesota Hazardous Substance List	8012-95-1	0.1 - 1

Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

XVI. ADDITIONAL INFORMATION

Supersedes: 8/27/2014 5:12:31 PM

Revision Date: 9/4/2014 1:36:37 PM

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.