

## Safety Data Sheet Acetoxy Silicone Sealant - Clear

---

### SECTION 1: Identification

#### 1.1 Product identifier

Product name Acetoxy Silicone Sealant - Clear

Product number 9-4

#### 1.3 Recommended use of the chemical and restrictions on use

Recommended use: Adhesive, binding agents

#### 1.4 Supplier's details

Name Master Products  
Address 4635 Willow Drive  
Medina, MN 55340  
USA

Telephone 612-478-2360

#### 1.5 Emergency phone number(s)

814-442-2778

---

### SECTION 2: Hazard identification

#### 2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

#### 2.2 GHS label elements, including precautionary statements

Not a hazardous substance or mixture.

#### 2.3 Other hazards which do not result in classification

Not a hazardous substance or mixture.

---

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Other names / synonyms Silicone elastomer

**Hazardous components**

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

### 1. Silicon dioxide

Concentration >= 5 - < 10 % (Weight)  
CAS no. 7631-86-9

### 2. Distillates (petroleum), hydrotreated middle

Concentration >= 5 - < 10 % (Weight)  
CAS no. 64742-46-7

---

## SECTION 4: First-aid measures

### 4.1 Description of necessary first-aid measures

General advice	Notes to physician: Treat symptomatically and supportively.
If inhaled	If inhaled, remove to fresh air.
In case of skin contact	Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Personal protective equipment for first-aid responders	No special precautions are necessary for first aid responders.

### 4.2 Most important symptoms/effects, acute and delayed

None known.

---

## SECTION 5: Fire-fighting measures

### 5.1 Suitable extinguishing media

Water spray  
Alcohol-resistant foam  
Dry chemical  
Carbon dioxide (CO<sub>2</sub>)

### 5.2 Specific hazards arising from the chemical

Exposure to combustion products may be a hazard to health.

### 5.3 Special protective actions for fire-fighters

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

Evacuate area.  
Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### Further information

Hazardous combustion products:  
Carbon oxides  
Silicon oxides  
Formaldehyde

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

### Reference to other sections

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Use only with adequate ventilation.

Handle in accordance with good industrial hygiene and safety practice.  
Take care to prevent spills, waste and minimize release to the environment.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

Do not store with the following product types:  
Strong oxidizing agents

---

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

**1. Silicon dioxide (CAS: 7631-86-9)**

TWA (Inhalation): 20 million particles per cubic foot (Silica) (OSHA)

**2. Silicon dioxide (CAS: 7631-86-9)**

TWA (Inhalation): 80 mg/m<sup>3</sup> / %SiO<sub>2</sub> (Silica) (OSHA)

**3. Silicon dioxide (CAS: 7631-86-9)**

TWA: 6 mg/m<sup>3</sup> (Silica) (NIOSH)

**4. Distillates (petroleum), hydrotreated middle (CAS: 64742-46-7)**

TWA (Inhalation): 5 mg/m<sup>3</sup> (OSHA)

**5. Distillates (petroleum), hydrotreated middle (CAS: 64742-46-7)**

TWA (Inhalation): 5 mg/m<sup>3</sup> (OSHA)

**6. Distillates (petroleum), hydrotreated middle (CAS: 64742-46-7)**

TWA (Inhalation): 5 mg/m<sup>3</sup> (NIOSH)

**7. Distillates (petroleum), hydrotreated middle (CAS: 64742-46-7)**

ST (Inhalation): 10 mg/m<sup>3</sup> (NIOSH)

#### 8.2 Appropriate engineering controls

Processing may form hazardous compounds (see section 10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

#### 8.3 Individual protection measures, such as personal protective equipment (PPE)

##### Eye/face protection

Wear the following personal protective equipment:

Safety glasses

##### Skin protection

Skin should be washed after contact.

Wash hands before breaks and at the end of workday.

##### Body protection

When using do not eat, drink or smoke.

Wash contaminated clothing before re-use.

##### Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Environmental exposure controls

Ensure that eye flushing systems and safety showers are located close to the working place.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

---

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance/form	Paste
Odor	Acetic acid
Odor threshold	No data available
pH	Not applicable
Melting point/freezing point	No data available
Initial boiling point and boiling range	Not applicable
Flash point	>100 degrees C closed cup
Evaporation rate	Not applicable
Flammability (solid, gas)	Not classified as a flammability hazard
Upper/lower flammability limits	No data available
Upper/lower explosive limits	No data available
Vapor pressure	Not applicable
Vapor density	No data available
Relative density	1.007
Solubility(ies)	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Use at elevated temperatures may form highly hazardous compounds.

Can react with strong oxidizing agents.

Acetic acid is formed upon contact with water or humid air.

When heated to temperatures above 150 °C (300 °F) in the

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

presence of air, trace quantities of formaldehyde may be released.  
Adequate ventilation is required.  
See OSHA formaldehyde standard, 29 CFR 1910.1048  
Hazardous decomposition products will be formed at elevated temperatures.

### 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

Oxidizing agents

### 10.6 Hazardous decomposition products

Formaldehyde

---

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

Acute inhalation toxicity : Acute toxicity estimate: > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

Ingredients:

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhalation toxicity

Remarks: Information taken from reference works and the literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Information taken from reference works and the literature.

Distillates (petroleum), hydrotreated middle:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.78 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Silicon dioxide:

Result: No skin irritation

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

Remarks: Information taken from reference works and the literature.

### **Serious eye damage/irritation**

Not classified based on available information.

Ingredients:

Silicon dioxide:

Result: No eye irritation

Remarks: Information taken from reference works and the literature.

### **Respiratory or skin sensitization**

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Ingredients:

Silicon dioxide:

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: No known sensitizing effect.

Information taken from reference works and the literature.

### **Germ cell mutagenicity**

Not classified based on available information.

Ingredients:

Silicon dioxide:

Genotoxicity in vitro : Result: negative

Remarks: Information taken from reference works and the literature.

Genotoxicity in vivo : Application Route: Ingestion

Result: negative

Remarks: Information taken from reference works and the literature.

Germ cell mutagenicity - Assessment

: Animal testing did not show any mutagenic effects.

### **Carcinogenicity**

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

Reproductive toxicity: Not classified based on available information.

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

STOT-repeated exposure: Not classified based on available information.

### **Aspiration hazard**

Aspiration toxicity: Not classified based on available information.

Ingredients:

Distillates (petroleum), hydrotreated middle:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## **SECTION 12: Ecological information**

### **Toxicity**

No data available

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

No data available

---

## **SECTION 13: Disposal considerations**

### **Disposal of the product**

Resource Conservation and Recovery Act (RCRA):

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

### **Disposal of contaminated packaging**

Dispose of as unused product.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## **SECTION 14: Transport information**

### **DOT (US)**

Not dangerous goods



# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

### IMDG

Not dangerous goods

### IATA

Not dangerous goods

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No	Component RQ (lbs)	Calculated Prodcut RQ (lbs)
Acetic Acid	64-19-7	5000	*
Acetic anhydride	108-24-7	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 311/312 Hazards

No SARA Hazards

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold reporting levels established by SARA Title III, Section 313

#### US State Regulations

##### Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated 70131-67-8 70 - 90 %

Silicon dioxide 7631-86-9 5 - 10 %

Distillates (petroleum), hydrotreated middle 64742-46-7 5 - 10 %

Acetic acid 64-19-7 0 - 0.1 %

Acetic anhydride 108-24-7 0 - 0.1 %

##### New Jersey Right To Know

Dimethyl siloxane, hydroxy-terminated 70131-67-8 70 - 90 %

Silicon dioxide 7631-86-9 5 - 10 %

Distillates (petroleum), hydrotreated middle 64742-46-7 5 - 10 %

Dimethyl siloxane, trimethylsiloxy-terminated 63148-62-9 1 - 5 %

##### California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### 15.2 Chemical Safety Assessment

# Safety Data Sheet

## Acetoxy Silicone Sealant - Clear

### The ingredients of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.  
IECSC : All ingredients listed or exempt.  
PICCS : All ingredients listed or exempt.  
DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).  
REACH : All ingredients (pre-)registered or exempt.  
TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

---

## SECTION 16: Other information

**NFPA:** Flammability 1, Health 1, Instability 0

**HMIS:** Health 1, Flammability 1, Physical Hazard 0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

### Full text of other abbreviations

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limitsfor Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

Sources of key data used to

compile the Material Safety

Data Sheet: Internal technical data, data from raw material SDSs, OECD

eChem Portal search results and European Chemicals Agency,

<http://echa.europa.eu/>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.